2-1/2" ACME THREAD

LEAD ACCURACY: ±0.0003 in./in.

LOAD CAPACITY (lbs.)	DYNAMIC	STATIC	
BRONZE NUT	31,250	100,000	
PLASTIC NUT	15,625	15,625	


			SCREW SIZE				
PRODUCT SPECIFICATIONS		2 ¹ /2"-2	2 ¹ /2"-3	2 ¹ /2"- 4			
Lead			.500	.333	.250		
Pitch			.500	.333	.250		
Starts			1	1	1		
Threads Per Inch		2	3	4			
Lash (Maximum Axial)		.012	.013	.012			
"A" – Root Diameter (min.)			1.908	2.106	2.193		
"B" – Nut Body Length		3.38	4.25	3.38			
Weight (lbs./ft.)			13.41	14.38	14.89		
Thread Code			252	253	254		
Form			40°	20	20		
36"	BU	4140	11252	11253	11254		
Standard Length Part No.*	RH	Stainless	_	_			
	LH	4140	51252	51253	51254		
		Stainless					
72" Standard Length Part No.*	RH	4140	12252	12253	12254		
		Stainless		—			
	LH	4140	52252	52253	52254		
4.4.40		Stainless			13254		
Length	RH	4140 Stainless	13252	13253	13254		
		4140	53252	53253	53254		
	LH	Stainless					
* Custom Lengths Available - See page 15 to specify length							
BRONZ/AC BRONZE NUT			2 ¹ /2"- 2	2 ¹ /2"-3	2 ¹ /2"-4		
Efficiency		34%	25%	20%			
Torque to Raise 1 lb. (inlb.)		.234	.212	.199			
Weight (lbs.)		5.00	5.91	4.55			
Part No.	Part No. RH		20252	20253	20254		
LH			80252	80253	80254		
PLAST/AC PLASTIC NUT		2 ¹ /2"-2	2 ¹ /2"-3	2 ¹ /2"-4			
Efficiency		40%	30%	24%			
Torque to Raise 1 lb. (inlb.)		.201	.174	.163			
Weight (lbs.)		.73	.86	.66			
Part No. RH		30252	30253	30254			
	LH		40252	40253	40254		
FLANGE - STEEL		2 ¹ /2"-2	2 ¹ /2"-3	2 ¹ /2"-4			
Weight (lbs.)		9.88	9.88	9.88			
Standard Part No.		70540	70540	70540			

73540

73540


73540





ACME SCREW ASSEMBLIES


These assemblies are shipped with screw, nut, flange, and bearing supports.



See page 41 for complete product details.

EZZE-MOUNT™ END BEARING SUPPORTS

A convenient solution for mounting acme screw assemblies.





Single or Double Bearing Universal Mount Single or Double Bearing Flange Mount

EZZE-MOUNT™ available for: 2-1/2"-2 See page 214 for complete product details.

TWIN-LEAD SCREW

Single piece twin-lead screws offer opposing motion through a single drive system.



Twin-Lead Screw available for: All 2-1/2" Screws See page 44 for complete product details.

LUBRICANT

Prolong acme screw and nut performance with these special lubricants.



E-100 12 0z. Acme Screw Spray Lubricant



See page 14 for complete product details.

No-Lash™ Part No.

The specifications and data in this publication are believed to be accurate and reliable. However, it is the responsibility of the product user to determine the suitability of Nook Industries products for a specific application. While defective products will be replaced without charge if promptly returned, no liability is assumed beyond such replacement.